

9500HS SAMURAI

HIGH SPEED WINCHES



Revolutionary design external brake.

Fully sealed to IP68 Standard.

600 amp silver tip contactors.

Solid Brass Contacts Direct to the Motor.

Laser etched extruded aluminium tie bars.

Silver Copper Motor with Copper Brush Holders

INCLUDED



12V only



WIRE ROPE AVAILABLE



Our premium "Next Generation" Samurai range are even faster, with a lower current draw and now boast a revolutionary external brake, more capable of load holding & lowering, as well as ensuring there's no heat build up in the drum, perfect for Armortek Ropes. The Samurai HS (High Speed) is fully sealed with an unbeatable line Speed of 40 ft/min.

STANDARD ACCESSORIES

- ③ Galvanised Steel Cable or Synthetic Rope
- ③ 3.8m Remote Handset
- ③ Aluminium or Stainless Steel Fairlead
- ③ Heavy Duty Battery Leads
- ③ Isolation Switch
- ③ Stainless Steel Mounting Hardware
- ③ Built In Wireless remote (12v only)
- ③ Heavy Duty Hook

OUTSTANDING FEATURES

- ③ External Brake.
- ③ All Brass (no corrosion) Series Wound Motor
- ③ Double Sealed Motor
- ③ Sealed Waterproof Contactor
- ③ Reinforced Plastic Contactor Cover
- ③ Double Sealed Drum (Gearbox/Motor)
- ③ Sealed 3 Stage Planetary Gears)

TECHNICAL SPECIFICATIONS

Model	Line Pull	Motor (12v)	Speed (No load) ft (m) p/min	Gearing	Drum (DxL)	Cable (DxL)	Size	Weight
HIGH SPEED 95VHSS12/24 95VHSA12/24	9500 lbs (4500 kg)	8.6hp 6.4kw	39.4(12)	196:1	63 x 223mm	9.2mm x 26m (W) 9.5mm x 25m (SR)	593 x 160 x 248mm	32 kg (W) 22 kg (SR)